

M18 PORTABLE OZONE SYSTEM

Portable ozonated water production for tank sanitization, surface disinfection and other applications has never been easier or more cost effective. Pacific Ozone Technology, the industry leader in air-cooled corona discharge ozone generators, has put its revolutionary technology in a compact, durable and completely mobile unit that offers the ozone production you'd expect from a permanent installation.

The M18 Portable Ozone System is a rugged, all stainless steel package that uses a Pacific Ozone Technology 18 g/hr (1 lbs/day) high concentration ozone/oxygen system with onboard pump and injector for efficient ozone mass transfer. Simply connect plant water in and get high concentration ozonated water out with no loss of flow or pressure.

The M18 allows for specific application of your required ozone production at various sites within a single facility, or even at multiple locations for diverse on-site applications.

Employing the same distinctive features and controls as Pacific Ozone's standard ozone generators, the M18 is a fully-functional that works great wherever you put it, with no letdown in water pressure or ozone concentration.

THE STANDARD M18 SYSTEM INCLUDES

- All stainless steel construction
- Water resistant enclosure
- Onboard air compressor
- Onboard oxygen concentrator
- Onboard booster pump
- Onboard side stream injector
- Automatic flow switch



M18 PORTABLE OZONE SYSTEM

FEATURES

0-100 gpm water flow
Operating Pressure to 85 psi
Air-Cooled Ceramic and Titanium Reactor Cell
Patented Floating Plate Technology™
5-Micro Filter/Regulator with Auto Drain
50' power connection cable
Optional Off-Gas Decomposer

CONTROLS

Variable Output Control 0-100%
Automatic Flow Switch
Over-Temperature Safety Switch
Automatic Door Switch
Feed Gas Flow Control
LED Visual Ozone Indicator

M18 PORTABLE OZONE SYSTEM

ProductDescription: Portable Automatic Ozone Contact System

Part Number: R-CAM181 115Vmodel
R-CAM182 230Vmodel

Specifications:

Ozone Production10scfh: 18 g/hr – 1.0 lbs/day
Oxygen Concentration: +90% @ 10 scfh
Water Flow Range: 5 – 100 gpm
Maximum Water Pressure: 85 psi
Water Inlet Connection: 1.5" Sanitary Fitting
Water Outlet Connection: 1.5" Sanitary Fitting
Feed Gas Flow Range: 0–20 scfh
Variable Control: 0–100%
Power Consumption: 1750 watts
Power Supply Fuse: 8 ampere
Air Cooling: 240 scfm
Power Cord: 50'
Power Requirement: 115V or 230V 50/60Hz 1 phase
Height: 39 inches
Width: 25 inches
Length: 37 inches
Weight: 210 lbs.



M18 PORTABLE OZONE SYSTEM

OPTIONS
Portable Ozone Off-Gas Detector
Ozone Degas Chamber
Catalytic Ozone Decomposer



EQUIPOS ESPECIALIZADOS DEL ATLANTICO SA de CV

PASEO LOMAS DE ROSALES #307 COL. LOMAS DE ROSALES C.P. 89100 TAMPICO, TAM. MÉXICO

TEL. - (833) 116-54-10

www.eatlantico.com

e-mail: marte.alvarez@atlantico.com